



深圳市思迪科科技有限公司

SHENZHEN CDTECH ELECTRONICS

Product Specification

Model Name	S101BWX42NP V3.0
Description	800(RGB)x1280 Dots 10.1" TFT LCD
Date	2022/05/10
Revision	1.0

Approved by/Date	Check by/Date	Prepared by/Date
ZHP 2022/05/10	HL 2022/05/10	ZWF 2022/05/10

Customer Approval	
Date	



Table of Contents

1. Record of Revision	3
2 General Specifications	4
3 Input/Output Terminals	5
4 Absolute Maximum Ratings	6
5 Electrical Characteristics	6
6 Optical Characteristics	12
7 Environmental / Reliability Tests	16
8 Mechanical Drawing	18
9 Packing	19
10 Precautions for Use of LCD modules	20



深圳市思迪科科技有限公司

SHENZHEN CDTECH ELECTRONICS

1. Record of Revision

Rev	Issued Date	Description	Editor
1.0	2022/05/10	First Release.	ZWF

2 General Specifications

Feature		Spec
Characteristics	Size	10.1 inch
	Resolution	800(Horizontal)*1280(Vertical)
	Interface	MIPI
	Connect type	Connector
	Color Depth	16.7M
	Technology type	a-Si
	Display Spec. Pixel pitch (mm)	0.169(H)*0.169(V)
	Pixel Configuration	R.G.B. Vertical Stripe
	Display Mode	Normally Black
	Driver IC	ILI9881C
	Viewing Direction	full view
Mechanical	LCM (W x H x D) (mm)	143.0(W)*228.6(H)*2.6 (D)
	Active Area(mm)	135.36(H)x 216.58(V)
	With /Without TSP	Without TSP
	Weight (g)	TBD
	LED Numbers	28 LEDs

Note 1: Viewing direction is follow the data which measured by optics equipment.

Note 2: Requirements on Environmental Protection: RoHS

Note 3: LCM weight tolerance: +/- 5%

3 Input/Output Terminals

LCD PIN-MAP

No	Symbol	Description
1	NC	No connect
2-3	VDD(3.3)	Power supply for logic operation
4	NC	No connect
5	RST	Device reset signal
6	NC	No connect
7	GND	GROUND
8	MIPI_D2N	MIPI Negative data signal(-)
9	MIPI_D2P	MIPI Positive data signal(+)
10	GND	GROUND
11	MIPI_D1N	MIPI Negative data signal(-)
12	MIPI_D1P	MIPI Positive data signal(+)
13	GND	GROUND
14	MIPI_CKN	MIPI Negative clock signal(-)
15	MIPI_CKP	MIPI Positive clock signal(+)
16	GND	GROUND
17	MIPI_D0N	MIPI Negative data signal(-)
18	MIPI_D0P	MIPI Positive data signal(+)
19	GND	GROUND
20	MIPI_3N	MIPI Negative data signal(-)
21	MIPI_3P	MIPI Positive data signal(+)
22	GND	GROUND
23-24	NC	No connect
25	GND	GROUND
26-29	NC	No connect
30	GND	GROUND
31-32	LED-	LED-
33-38	NC	No connect
39-40	LED+	LED anode

4 Absolute Maximum Ratings

Item	Symbol	MIN	Typ	MAX	Unit	Remark
Supply Voltage	VDD	-0.3	-	5.0	V	-
Operating Temperature	TOPR	-20	-	70	°C	-
Storage Temperature	TSTG	-20	-	70	°C	

5 Electrical Characteristics


5.1 Driving TFT LCD Panel

Item	Symbol	MIN	Typ	MAX	Unit	Remark
Supply Voltage	VDD	3.0	3.3	3.6	V	-
Current of power supply	I _{VDD}	-	140	160	mA	-
Input voltage "H" level	VIH	0.7VDD	-	VDD	V	
Input voltage "L" level	VIL	0	-	0.3VDD	V	


5.2 POWER ON/OFF SEQUENCE

To prevent the device damage from latch up and Improve subjective display effect, the power ON/OFF sequence shown below must be followed.

Case A:



Case B:



Symbol	Characteristics	Min.	Typ.	Max.	Units
T_{VDDI_RISE}	VDDI Rise time	10	-	-	us
T_{VCI_RISE}	Case A: VCI Rise time	130	-	-	us
	Case B: VCI Rise time	40			
T_{PS_RES}	VDDI/VCI on to Reset high	5	-	-	ms
T_{RES_PULSE}	Reset low pulse time	10	-	-	us
T_{FS_CMD}	Reset to first command	10	-	-	ms

Figure 93: Power on/off sequence with Power Mode 3


5.3 Driving Backlight

Item	Symbol	MIN	TYP	MAX	Unit	Remark
Forward Current	I_F	-	100	-	mA	
Forward Voltage	V_F	18.9	-	23.8	V	
Backlight Power consumption	W_{BL}	1.89	-	2.38	W	
LED Lifetime		-	30000	-	Hrs	

Note 1: Each LED : $I_F = 25 \text{ mA}$, $V_F = 2.7 \sim 3.4 \text{ V}$.

Note 2: Optical performance should be evaluated at $T_a = 25^\circ \text{C}$ only.


Note 3: If LED is driven by high current, high ambient temperature & humidity condition. The life time of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating life time is estimated data.



CIRCUIT DIAGRAM

Figure : LED connection of backlight

5.4 RESET TIMING CHARACTERISTICS



Reset Timing

Signal	Symbol	Parameter	Min	Max	Unit
RESX	t_{RW}	Reset pulse duration	10		μ S
	t_{RT}	Reset cancel		TBD (note 1,5)	mS
				TBD (note 1,6,7)	mS

Notes:

1. The reset cancel also includes required time for loading ID bytes, VCOM setting and other settings from EEPROM to registers. This loading is done every time when there is HW reset cancel time (t_{RT}) within 5 ms after a rising edge of RESX.
2. Spike due to an electrostatic discharge on RESX line does not cause irregular system reset according to the
- 3.

Reset Descript

RESX Pulse	Action
Shorter than 5us	Reset Rejected
Longer than 10us	Reset
Between 5us and 10us	Reset starts

4. During the Resetting period, the display will be blanked (The display enters the blanking sequence, which maximum time is 120 ms, when Reset Starts in the Sleep Out mode. The display remains the blank state in the Sleep In mode.) and then return to Default condition for Hardware Reset.

5.5 MIPI-DSI CHARACTERISTICS

5.5.1 High speed mode





Figure 4: DSI Clock Channel Timing

DSI Clock Channel Timing

Signal	Symbol	Parameter	Min	Max	Unit
CLKP/N	$2xUI_{INST}$	Double UI instantaneous	TBD	TBD	ns
CLKP/N	UI_{INSTA}, UI_{INSTB} (Note 1)	UI instantaneous Half	TBD (Note 2)	TBD	ns

5.5.2 High Speed Mode – Data Clock Channel Timing




DSI Data to Clock Channel Timings

DSI Data to Clock Channel Timings

Signal	Symbol	Parameter	Min	Max
DnP/N, n=0 and 1	t_{DS}	Data to Clock Setup time	TBD	-
	t_{DH}	Clock to Data Hold Time	TBD	-

5.5.3 High Speed Mode – Rising and Falling Timings



Rising and Falling Timings on Clock and Data Channels

Rise and Fall Timings on Clock and Data Channels

Parameter	Symbol	Condition	Specification		
			Min	Typ	Max
Differential Rise Time for Clock	t_{DFTCLK}	CLKP/N	TBD	-	TBD (Note)
Differential Rise Time for Data	$t_{DFTDATA}$	DnP/N n=0 and 1	TBD	-	TBD (Note)
Differential Fall Time for Clock	t_{DFTCLK}	CLKP/N	TBD	-	TBD (Note)
Differential Fall Time for Data	$t_{DFTDATA}$	DnP/N n=0 and 1	TBD	-	TBD (Note)

Note: The display module has to meet timing requirements, which are defined for the transmitter (MCU) on MIPI D-Phy standard.

6 Optical Characteristics


Items		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing angles		θ_T	Center CR≥10	75	80	-	Degree.	Note2
		θ_B		75	80	-		
		θ_L		75	80	-		
		θ_R		75	80	-		
Contrast Ratio		CR	$\Theta =0$	800	1000	-	-	Note1, Note3
Response Time		T _{ON}	25°C	-	30	35	ms	Note1, Note4
		T _{OFF}						
Chromaticity	White	X _W	Backlight is on	0.254	0.304	0.354	-	Note1, Note5
		Y _W		0.270	0.320	0.370	-	
Uniformity		U		70	75	-	%	Note1, Note6
Luminance		L		350	400		cd/m2	Note1, Note7

Test Conditions:

1. IF= 20mA(one channel),the ambient temperature is 25°C.
2. The test systems refer to Note 1 and Note 2.

Note 1:Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



Note 2: Definition of viewing angle range and measurement system.
viewing angle is measured at the center point of the LCD by CONOSCOPE(ergo-80).




Fig. 1 Definition of viewing angle

Note 3: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD is on the "White" state}}{\text{Luminance measured when LCD is on the "Black" state}}$$


“White state”: The state is that the LCD should driven by V_{white} .

“Black state”: The state is that the LCD should driven by V_{black} .

V_{white} : To be determined V_{black} : To be determined.

Note 4: Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of LCD.

Note 6: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity}(U) = L_{min} / L_{max} \times 100\%$$

L-----Active area length W----- Active area width




Fig. 2 Definition of uniformity

Lmax: The measured maximum luminance of all measurement position.

Lmin: The measured minimum luminance of all measurement position.

Note 7: Definition of Luminance :

Measure the luminance of white state at center point.

7 Environmental / Reliability Tests

No	Test Item	Condition	Remarks
1	High Temperature Operation	Ts= +70℃, 96hrs	IEC60068-2-1:2007 GB2423. 2-2008
2	Low Temperature Operation	Ta= 20℃, 96hrs	IEC60068-2-1:2007 GB2423.1-2008
3	High Temperature Storage	Ta= +70℃, 96hrs	IEC60068-2-1:2007 GB2423. 2-2008
4	Low Temperature Storage	Ta= -20℃, 96hrs	IEC60068-2-1:2007 GB2423.1-2008
5	High Temperature & Humidity Operation	Ta= +40℃, 80% RH max, 96 hours	IEC60068-2-78:2001 GB/T2423.3-2006
6	Thermal Shock (Non-operation)	-30℃ 30 min ~ +80℃ 30 min Change time: 5min, 20 Cycle	Start with cold temperature, end with high temperature IEC60068-2-14:1984, GB2423.22-2002
7	ESD	C=150pF, R=330 Ω, 5 points/panel , Air:±8KV, 5 times Contact: ±4KV, 5 times (Environment: 15℃ ~ 35℃, 30% ~ 60%, 86Kpa ~ 106Kpa)	IEC61000-4-2:2001 GB/T17626.2-2006
8	Vibration (Non-operation)	Frequency range: 10~55Hz, Stroke: 1.5mm , Sweep: 10Hz~55Hz~10Hz 2 hours for each direction of X .Y. Z. (6 hours for total)	IEC60068-2-6:1982 GB/T2423.10-1995
9	Mechanical Shock (Non-operation)	Half Sine Wave 60G ,6ms,±X,±Y,±Z 3times for each direction	IEC60068-2-27:1987 GB/T2423.5—1995
10	Package Drop Test	Height: 60 cm, 1 corner, 3 edges, 6 surfaces	IEC60068-2-32:1990 GB/T2423.8-1995




深圳市思迪科科技有限公司

SHENZHEN CDTECH ELECTRONICS

Notes:


1. The test result shall be evaluated after the sample has been left at room temperature and humidity for 2 hours without load. No condensation shall be accepted. The sample will not be accepted if appear these defects:
 - 1).Air bubble in the LCD;
 - 2).Seal leak
 - 3).Non-display
 - 4).missing segments
 - 5).Glass crack
 - 6).CR reduction >40%
 - 7).IDD increase >100%
 - 8).Brightness reduction >50%
 - 9).Color coordinate tolerance >0.05
- 2.≤7.0 inch: The size of sample is 5pcs;
 >7.0 inch: The size of sample is 2pcs;
3. One test sample must complete each test item;
- 4.In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judge as a good part.
- 5.In the test of High Temperature Operation and High Temperature & Humidity Operation ,the operation temperature is the surface temperature of module.

8 Mechanical Drawing



9 Packing

Packing Method



1. Put module into tray cavity:
2. Tray stacking
3. Put 1 cardboard under the tray stack and 1 cardboard above:
4. Fix the cardboard to the tray stack with adhesive tape:
5. Put the tray stack into carton.
6. Carton sealing with adhesive tape.

10. Precautions for Use of LCD modules

10.1 Handling Precautions

10.1.1. The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

10.1.2. If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

10.1.3. Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

10.1.4. The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

10.1.5. If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketene

10.1.6. Do not attempt to disassemble the LCD Module.

10.1.7. If the logic circuit power is off, do not apply the input signals.

10.1.8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

10.1.8.1. Be sure to ground the body when handling the LCD Modules.

10.1.8.2. Tools required for assembly, such as soldering irons, must be properly ground.

10.1.8.3. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

10.1.8.4. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

10.2 Storage Precautions

10.2.1. When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

10.2.2. The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0℃ ~ 40℃ Relatively humidity: ≤80%

10.2.3. The LCD modules should be stored in the room without acid, alkali and harmful gas.

10.3 Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.